



# AQUAGUSTO – QUALITY COFFEE AND FILTER EXCHANGE ALWAYS IN VIEW

Technology: Decarbonisation

## A practical filter solution for coffee and espresso machines with water tank

Whether in HoReCa or in the office, the BRITA AquaGusto water tank filter will enhance the flavour, aroma and appearance of coffee. And, of course, that also applies to espresso and cappuccino. The filter can be used in almost any coffee machine and reduces limescale deposits. It is impressively simple and quick to operate and users also benefit from the added filter exchange signal.

### Forgetting to change the filter is now a thing of the past

The filter change signal means you always know the right time to change the filter. Simply place the filter change signal in a visible location and press the button firmly.



### Your benefits: reminder function for simple operating.

- Can be used in all conventional water tanks: no adapter, no assembly
- Easy to use: simply place in the tank and allow to stand
- Including automatic filter change signal – for better service
- Simple and immediate filter installation and exchange by the user
- Enhanced coffee flavour, aroma and appearance
- Reduces limescale deposits

# AquaGusto

## Versatile operation

AquaGusto filters are suitable for use in all coffee machines with a water tank.



The food safety of BRITA Professional water filter products is tested and monitored by independent institutes.


### Using the filter exchange display




Stick the filter exchange display to the water tank and press the start button firmly.



When a red line is visible, the filter exchange display is activated.



The red zone extends over time until the maximum period of use has been reached.



After approx. six months, the maximum period of use has been reached and the filter must be exchanged.

Product	Order number
Pack 1 AquaGusto 100 CU	1018872
Pack 1 AquaGusto 250 CU	1018881
Pack 60 AquaGusto 100 CU	1018885
Pack 60 AquaGusto 250 CU	1018888

	AquaGusto	
	100	250
Dimensions (width/depth)	85.1/25.8mm	115.5/32.9mm
Capacity*/Period of use*	100l/max. 6 months	250l/max. 6 months
Water input temperature	4–30°C	
Position in tank	horizontal/vertical	

\*The capacities given have been tested and calculated on the basis of normal application and machine conditions. Due to external influences (e.g. varying water quality, usage and/or machine type) deviations from these results can occur.

Only drinking quality water may be used as the water supply for BRITA water filters.

**Headquarters**  
BRITA GmbH  
Heinrich-Hertz-Straße 4  
D – 65232 Taunusstein

BRITA Water Filter Systems Ltd.  
BRITA House  
9 Granville Way  
Bicester  
GB – Oxfordshire OX26 4JT  
tel.: +44 (0) 844 742 4990 | fax: +44 (0) 844 742 4902  
clientservices@brita.co.uk  
www.brita.co.uk

